



Specifications:

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
LF-113	AMP-180	3100 / 1406	100 / 30	870 / 394	45 / 114	29 / 74	27 / 69

Rated Capacity	Max. Pull At Stall (1st Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
100 PSIG	6,400 lbs	530 cfm	18 HP

Rope Capacity

Rope capacity includes 20% for rough winding.					
Tugger Model	Drum Size	3/8" / 9.5 mm	1/2" / 12.7 mm	5/8" / 15.9 mm	3/4" / 19.1 mm
LF-113	18"	2400 ft / 732 m	1400 ft / 427 m	1125 ft / 343m	765 ft / 233m

NOTE: *STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, REVERSING THROTTLE VALVE W/Self Centering Control, HAND OPERATED TOGGLE HAND BRAKE, MANUAL ENGAGED GEAR CLUTCH FOR FREE SPOOLING OF DRUM
 *OPTIONAL EQUIPMENT: EXHAUST MUFFLER, REMOTE CONTROL THROTTLE VALVE, MARINE PROTECTIVE EPOXY PAINT.



NELMACO EASTERN LTD

Sudbury, ON Canada

Tel: 705-560-3705

Fax: 705-560-6983

Email: info@nelmaco.com **Website:** www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS